

Luminaire Data Sheet


Apus




Highbay offers class leading efficiency
 Die cast aluminum
 polycarbonate diffuser
 For use in most industrial applications.
 Options with integral control



- 50,000 hrs to L90
- CCT 4000K
- CRI > 80
- IP65, IK10
- Power Factor > 0.95
- Operating Temp -40°C + 50°C
- Insulation Class I
- 5 year warranty



Area 90°



Narrow 60°

Code	Description	Luminaire Lumens	Inrush Current	Current (A)	Qty / Type C 10A breaker	Dimensions W x H (mm)	L x	Weight (kg)
AP/161040/AR	Apus, 230V, 100W, Area 90°	2268	55A / 500µs	0.43	8	362 x 257 x 120		4.5
AP/161040/NA	Apus, 230V, 100W, Narrow 60°	2674	55A / 500µs	0.43	8	362 x 257 x 120		4.5
AP/241540/AR	Apus, 230V, 150W, Area 90°	3742	60A / 500µs	0.65	5	487 x 362 x 120		6.5
AP/241540/NA	Apus, 230V, 150W, Narrow 60°	5348	60A / 500µs	0.65	5	487 x 362 x 120		6.5
AP/322040/AR	Apus, 230V, 200W, Area 90°	4678	65A / 500µs	0.87	4	487 x 362 x 120		6.5
AP/322040/NA	Apus, 230V, 200W, Narrow 60°	6685	65A / 500µs	0.87	4	487 x 362 x 120		6.5