


Luminaire Data Sheet

Indus



- 50,000 hrs to L70
- Aluminium construction with PS diffuser
- CCT 4000K
- CRI>80
- IP40, IK02
- SDCM <6
- Power Factor >0.9
- Operating Temp -20°C to 40°C
- Insulation Class II
- Options for DALI
- 5 year warranty



Code	Description	Luminaire Lumens	Inrush Current	Current (A)	Qty Type C 10A breaker	Weight (kg)	Dimensions L x W x H (mm)
IND211940-MP	Indus lay-in, 230V, 19W	2131	16A / 220µs	0.08	41	2.6	595 x 595 x 40
IND252340-MP	Indus lay-in, 230V, 23W	2509	16A / 220µs	0.10	33	2.6	595 x 595 x 40
IND302640-MP	Indus lay-in, 230V, 26W	2987	16A / 220µs	0.11	30	2.6	595 x 595 x 40
IND343040-MP	Indus lay-in, 230V, 30W	3412	16A / 220µs	0.13	25	2.6	595 x 595 x 40
IND383440-MP	Indus lay-in, 230V, 34W	3797	30A / 200µs	0.15	22	2.6	595 x 595 x 40
IND444040-MP	Indus lay-in, 230V, 40W	4419	30A / 200µs	0.17	19	2.6	595 x 595 x 40