

Luminaire Data Sheet

EBH-HO



A classically styled high output emergency bulkhead which can be surface mounted or semi-recessed. Suitable for a wide range of applications, tough and versatile.

- Available as maintained or non-maintained.
- 20mm conduit entry.
- IP65/IK10
- Cable gland and legend pack included.
- Recessing kit available.
- Remote control compatible.
- 8 year warranty including battery.
- Option for Self Test



Detail	EBH-HO
Mains Frequency	50 / 60 Hz
Max. Power Consumption	5W
Standby Power	< 0.5W
Emergency Output Power	6W
Lumen Output	811
Rated Emergency Duration	3 hours
Battery Charge Time	< 20 hours
Operating Temperature	0 to 40°C
Insulation Class	Class II
Ingress Protection	IP 65
Impact Protection	IK 10
Dimensions (L x W x H)	355 x 109 x 61mm
Battery Compatibility	4 x 18650 Li-ion 3.6V 10.0Ah
Rated Supply Voltage	220-240V AC



Luminaire Data Sheet

EBH-HO



SELF - TEST

Green LED	Red LED	Status
on	Off	Standby
Slow Flash	Off	Charging
Fast Flash	Off	Function test or duration test in progress
Off	On	Battery Disconnected / Duration Test
Off	Fast Flash	Battery temp out of operational range
Off	Slow Flash	Light source failure

Materials

Housing	Polycarbonate
Finish	Matt
Colour	White
Screws	Nickel Steel

LED Light Source

Type	2835
Colour Temp	4000K
CRI	>80
LED Lifetime	50,000 hrs

