

EBH is a range of traditional emergency bulkheads suitable for use in a wide variety of applications. EBH has a polycarbonate housing sealed to IP65 with IK10 impact rating, and a high efficiency diffuser. Available with options for DALI-2, and for maintained or non-maintained operation, EBH comes with a 50,000 hour service life backed by an industry leading 8 year warranty



## Key features

- Supplied with legend kit
- Industry leading 8 year warranty
- CCT - 4000K
- CRI: >80
- Sealed to IP65, Impact rating IK10
- 50,000 hours service life



## Order Guide

Code	Power (W)	Emergency Lumens	CCT (K)	Weight (kg)	Description	Dimensions (mm)		
						Length	Width	Height
EBH200/NM3	1.5	192	4000	0.6	3hr non-maintained	355	109	61
EBH200/M3	1.5	192	4000	0.6	3hr maintained	355	109	61
EBH300/NM3	3.0	321	4000	0.7	3hr non-maintained	355	109	61
EBH300/M3	3.0	321	4000	0.7	3hr maintained	355	109	61
EBH300/NM3/DD	3.0	321	4000	0.7	3hr non-maintained, DALI-2	355	109	61
EBH300/M3/DD	3.0	321	4000	0.7	3hr maintained, DALI-2	355	109	61

## Accessories

Code Suffix	Description
.../ST	Self test
EBH/SRK	Semi-recess kit, white. Cut-out 370mm x 130mm