

Luminaire Data Sheet


Rubix Suspended




Flexible range of linear luminaires designed to add a touch of style to any office or commercial space. Individual luminaires or continuous Lines. A simple and clean finished look. Microprism diffuser ensures a comfortable, low glare output.



- 100,000 hrs to L80/B10
- CCT 4000K (3000K Available)
- CRI > 80
- IP40, IK05
- SDCM 3
- Power Factor > 0.85
- Operating Temp ta 0..+35
- Insulation Class I
- 5 year warranty



Direct



Direct / Indirect

Code	Description	Luminaire Lumens	Luminaire Lumens (Emergency)	Inrush Current	Current (A)	Qty / Type C 10A breaker	Dimensions L x W x H (mm)	Weight (kg)
RX12S1-271940WH-MP	19W, Direct only,	2689	404	23A / 176µs	0.08	42	1215 x 175 x 40	4.1
RX12S1-352240WH-MP	22W, Direct only	3507	454	23A / 140µs	0.09	37	1215 x 175 x 40	4.1
RX12S1-453040WH-MP	30W, Direct only,	4570	434	23A / 140µs	0.13	26	1215 x 175 x 40	4.1
RX15S1-332240WH-MP	22W, Direct only,	3362	435	23A / 176µs	0.09	37	1495 x 175 x 40	5.1
RX15S1-432740WH-MP	27W, Direct only,	4383	462	23A / 140µs	0.11	30	1495 x 175 x 40	5.1
RX15S1-573740WH-MP	37W, Direct only,	5713	440	23A / 140µs	0.16	21	1495 x 175 x 40	5.1
RX12S2-402640WH-MP	26W, Direct / Indirect,	3997	438	5.5A / 20µs	0.11	30	1215 x 175 x 40	4.6
RX12S2-543940WH-MP	39W, Direct / Indirect,	5447	398	1.5A / 100µs	0.16	21	1215 x 175 x 40	4.6
RX12S2-634340WH-MP	43W, Direct / Indirect,	6372	422	11A / 38µs	0.18	19	1215 x 175 x 40	4.6
RX15S2-513440WH-MP	34W, Direct / Indirect,	5114	428	5.5A / 20µs	0.14	24	1495 x 175 x 40	5.6
RX15S2-694940WH-MP	49W, Direct / Indirect,	6968	405	15A / 100µs	0.21	16	1495 x 175 x 40	5.6
RX15S2-815440WH-MP	54W, Direct / Indirect,	8138	429	12A / 25µs	0.23	14	1495 x 175 x 40	5.6