

# Rubix Suspended

Rubix is a flexible range of linear luminaires designed to add a touch of style to any office or commercial space. Available as individual luminaires or in continuous lines, Rubix offers a simple and clean finished look. Cutting edge LED technology achieves impressive efficacy up to 150 lumens per Watt, and the microprism diffuser ensures a comfortable, low glare output. Rubix comes with a 50,000 hour service life backed by a 5 year warranty



## Key features

- Excellent efficacy, up to 150 lumens per Watt
- 5 year warranty
- 50,000 hours service life to L80/B10
- CCT - 4000K as standard. 3000K also available
- CRI >80

## Order Guide

Code	Power (W)	Luminaire Lumens	CCT (K)	Weight (kg)	Optic	Dimensions (mm)		
						Length	Width	Height
RX12S1-271940WH-MP	19	2689	4000	4.1	Direct only, microprism diffuser UGR<19	1215	175	40
RX12S1-352240WH-MP	22	3507	4000	4.1	Direct only, microprism diffuser UGR<19	1215	175	40
RX12S1-453040WH-MP	30	4570	4000	4.1	Direct only, microprism diffuser UGR<19	1215	175	40
RX15S1-332240WH-MP	22	3362	4000	5.1	Direct only, microprism diffuser UGR<19	1495	175	40
RX15S1-432740WH-MP	27	4383	4000	5.1	Direct only, microprism diffuser UGR<19	1495	175	40
RX15S1-573740WH-MP	37	5713	4000	5.1	Direct only, low glare microprism diffuser	1495	175	40
RX12S2-402640WH-MP	26	3997	4000	4.6	Direct / Indirect, microprism diffuser UGR<19	1215	175	40
RX12S2-543940WH-MP	39	5447	4000	4.6	Direct / Indirect, microprism diffuser UGR<19	1215	175	40
RX12S2-634340WH-MP	43	6372	4000	4.6	Direct / Indirect, microprism diffuser UGR<19	1215	175	40
RX15S2-513440WH-MP	34	5114	4000	5.6	Direct / Indirect, microprism diffuser UGR<19	1495	175	40
RX15S2-694940WH-MP	49	6968	4000	5.6	Direct / Indirect, microprism diffuser UGR<19	1495	175	40
RX15S2-815440WH-MP	54	8138	4000	5.6	Direct / Indirect, microprism diffuser UGR<19	1495	175	40

## Accessories

Code Suffix	Description
.../E3	3hr integral maintained emergency
.../DD	DALI driver
.../TW	Through wiring in continuous line
RX1SK15	Suspension wire, adjustable, 1.5m drop
RX1JK	Join kit for luminaires in continuous line
RX3B	Blank Infill Section 300mm
RX6B	Blank Infill Section 600mm
RX12B	Blank Infill Section 1215mm

